

# HOTBOX

## Mobile



- **Quick** and efficient heating
- 80Kw diesel burner
- Also available as 12 & 24 V

### Low pressure HOTBOX can be used for:

- Drinking water for animal husbandry
- Heating of diving suits
- CIPP Lining
- Can be connected to cold-water cleaner

MODEL	WORKING PRESSURE/BAR	WATER USAGE L/MIN.	DIESEL TANK	VOLTAGE	LENGTH MM.	WIDTH MM.	HEIGHT MM.	WEIGHT KG.
HOTBOX 025	25	45	20L	1x230	700	570	800	75
HOTBOX 200	200	11-28	20L	1x230	700	570	800	75
HOTBOX 300	300	11-28	20L	1x230	700	570	800	75
HOTBOX 400	400	11-28	20L	1x230	700	570	800	75
HOTBOX 500	500	11-28	20L	1x230	700	570	800	75
DB HOTBOX 025	025	90	20L	1x230	1000	680	800	150
DB HOTBOX 200	200	56	20L	1x230	1000	680	760	150
DB HOTBOX 300	300	56	20L	1x230	1000	680	760	150
DB HOTBOX 400	400	56	20L	1x230	1000	680	760	150
DB HOTBOX 500	500	56	20L	1x230	1000	680	760	150

## Stationary



- **Quick** and efficient heating
- 80Kw diesel burner
- Also available as 12 & 24 V



MODEL	WORKING PRESSURE/BAR	WATER USAGE L/MIN.	DIESEL TANK	VOLTAGE	LENGTH MM.	WIDTH MM.	HEIGHT MM.	WEIGHT KG.
ST HOTBOX 025	25	45	20L	1x230	500	340	800	75
ST HOTBOX 200	200	11-28	20L	1x230	500	340	800	75
ST HOTBOX 300	300	11-28	20L	1x230	500	340	800	75
ST HOTBOX 400	400	11-28	20L	1x230	500	340	800	75
ST HOTBOX 500	500	11-28	20L	1x230	500	340	800	75
ST DB HOTBOX 025	025	90	20L	1x230	1000	580	760	150
ST DB HOTBOX 200	200	56	20L	1x230	1000	580	760	150
ST DB HOTBOX 300	300	56	20L	1x230	1000	580	760	150
ST DB HOTBOX 400	400	56	20L	1x230	1000	580	760	150
ST DB HOTBOX 500	500	56	20L	1x230	1000	580	760	150